



## 12 VDC coil with Deutsch DT04-2P connector

Model: **770-912N** 







#### **Technical Features**

- This DC coil does not include a TVS surge suppression diode.
  Coils without TVS diodes should only be used when surge suppression is included elsewhere in the electrical system.
- Coil windings utilize Class N, (392° F [200 °C] rated) magnet wire.
- The external steel shell is zinc plated with black dichromate.
- RoHS compliant. Restricted materials less than 0.1% total by weight.

- For optimum proportional performance, an amplifier with current sensing and adjustable dither should be used. Dither should be adjustable between 100 - 250 Hz.
- The Deutsch DT04-2P connector satisfies the requirements of thermal shock tests. In this test, the coil is energized to achieve its stabilized temperature and then immediately immersed into ice cold water. This process is repeated 5 times, after which, the insulation resistance of the coils should not fall below 10 megohms.
- IP rating is dependent on the coil connector and the mating connector used.
- Power cable with mating connector is required and is not included with product.

### **Technical Data**

rechnical Data			
	U.S. Units	Metric Units	
Arc Suppression	Standard		
Maximum Ambient Temperature	122 °F	50 °C	
Maximum Coil Temperature at 68°F (20°C) Ambient	218°F (105°C)		
Power Consumption (cold) - at rated voltage	22 watts		
Voltage/Frequency	12 VDC		

Operating Voltage Range	+/- 10%	+/- 10% nominal		
Duty cycle Rating	100 %			
Connector	Deutsch DT04-2P			
Connector Environment Rating	IP69	IP69K		
Solenoid Tube Diameter	.75 in.	19 mm		
Coil Nut Torque	4.5 lbf in.	0,5 Nm		
Model Weight	0.53 lb.	0.24 kg.		

**Proportional Performance Data** 

	U.S. Units Metric Units
Maximum Current	1150 mA
Nominal Coil Resistance at 122°F (50°C) Stabilized	9.4 ±8% ohms
Nominal Coil Resistance at 68°F (20°C) Cold	6.4 ±8% ohms

# 770-912N

What mode	els can this kit be	e used on?					
DAAL	DLDAS	DMDAS	DNDAS	DTCAS	FMDA	HDDAS	PSDL
DAALS	DLDAZ	DMDAZ	DNDC	DTCAZ	FMDB	PRDL	PSDP
DBAL	DLDX	DNCA	DNDY	DTDA	FPCC	PRDM	RBAN
DBALS	DLDXS	DNCAZ	DNDYS	DTDAS	FPCH	PRDN	RBAP
DLDA	DMDA	DNDA	DTCA	DWDA	HDDA	PRDP	

### **Related Information**

Environmental Test Specification, S-367 in pdf format

### Instructions/Notes

• No Special Notes Available for selected model.