


Series P - T-8A cavity, buna-N, cartridge seal kit

Model: **990-008-007**



Technical Features

• The shelf life for a Buna-N cartridge seal kit is ten years from date of purchase. This date will be printed on the kit packaging.

Cartridge Installation Data

	U.S. Units	Metric Units
Cavity	T-8	A
Cartridge Thread	M1	6
Valve Hex Size	7/8 in.	22,2 mm
Valve Installation Torque	20 - 25 lbf ft	27 - 33 Nm

990-008-007

What	models	can	thic	Ŀi+	he	hazıı	on?

	DAAA	DAAL	FXAG	RBAE	XAAE	XACAE	XAOA
CXAA	DAAC	DAALS	NFAB	RBAR	XACA	XACC	

Display Components

	Description	Quantity	View
500-001-010	O-Ring	1	В
530-002-011	Glyd Ring	1	В
500-002-014	O-Ring	1	Α
515-002-014	Backup Ring	1	Α
999-019-094	Literature	1	

Instructions/Notes

- Install back-up rings and O-rings as shown in views.
- When installing continuous back-up rings, use the same technique and the same care used to install O-rings.
- After installing the GLYD® Ring, size it to restore original shape and to prevent damage during cartridge installation.
- When installing cartridge be sure to torque to recommended value.
- GLYD® Ring is a registered trademark of W. S. Shamban and Co., Los Angeles, CA, USA