


# R (cap with lockwire) control kit with sealed adjustment

Model: **991-064** 

Sun offers an R control replacement kit with the added benefit of maintaining min/max setting. This kit includes a sealed cap with lockwire and a stop ring where applicable. This kit can also be used to replace a J, M, and Q control.



#### **Technical Features**

Shelf life for Viton seals is 20 years from package date. Package date is printed on packaging material.

Technical Data		
	U.S. Units	Metric Units
For Cartridge Models	For Models with L, J, M, Q, & R Control (excluding counterbalance & Series 0)	
Material	Stainless Steel	
Seal Material	Viton	
Adjustment Locknut/Cap Hex Size	5/8 in.	16 mm
Model Weight	0.06 lb.	0.03 kg.

## 991-064

#### **Display Components**

	Description	Quantity
820-001	Lockwire	1
500-151-479	O-Ring	2
400-001-A05	Stop Ring	1
375-038-A00	Сар	1
350-045-A00	Locknut	1

### Instructions/Notes

- Release pressure within the valve.
- Set valve to minimum adjustment.
- Remove original wire stop ring (where applicable) and locknut.
- With face seal in groove, thread locknut onto adjust screw until it bottoms out on hex body.
- Install new wire stop ring through slot provided.
- Adjust valve to desired setting and install wire stop ring (where applicable).
- Install cap onto locknut, ensuring second locknut seal is in groove below thread. Tighten to 108 lbf in. (12 Nm).