



Fixed setting, 1.5:1 pilot ratio, ultra-restrictive counterbalance valve



Capacity:
2.5 gpm (10 L/min.)

Model:
CBABX

Product Description

Fixed-setting, 3-port counterbalance valves with pilot assist function similarly to the adjustable versions except the fixed setting is pre-set to a nominal value. These fixed-setting valves are meant to control an overrunning load. The check valve allows free flow from the directional valve (port 2) to the load (port 1) while a direct-acting, pilot-assisted relief valve controls flow from port 1 to port 2. Pilot assist at port 3 lowers the effective setting of the relief valve at a rate determined by the pilot ratio.

Other names for this valve include motion control valve and over center valve.





Technical Features

- Restrictive valves have no relief capacity other than as a thermal relief.
- Fixed-setting counterbalance valves can be used to protect cylinder seals in outrigger circuits from damage due to thermal expansion, however, they probably should not be applied in circuits in which a matched valve setting may be required such as dual cylinder applications.
- The maximum recommended load pressure for the N range is 2200 psi (150 bar). The highest cracking pressure for the N range will be less than 3500 psi (245 bar).
- This valve has positive seals between all ports.
- The maximum recommended load pressure for the P range is 1700 psi (120 bar). The highest cracking pressure for the P range will be less than 2680 psi (185 bar).
- Backpressure at port 2 adds to the effective relief setting at a ratio of 1 plus the pilot ratio times the backpressure.
- Note: The pressures listed under RANGE are approximate, mean values and should not be used for inspection purposes.
- All 3-port counterbalance, load control, and pilot-to-open check cartridges are physically interchangeable (i.e. same flow path, same cavity for a given frame size).
- Note: The percentage difference between the cracking and reseal values for the fixed and adjustable versions of this valve are identical. However, the cracking point for the adjustable control can be set via the adjustment mechanism to within +/- 50 psi (3,5 bar) of the specified value. In the case of the fixed-setting version, the setting tolerance can only be maintained within a several hundred psi span, depending on the range. The maximum recommended load pressure for any given range is the minimum possible setting divided by 1.3.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.
- Fixed-setting counterbalance valves offer a shorter cartridge extension than the adjustable version.

Technical Data

	U.S. Units	Metric Units
Cavity	T-11A	
Capacity	2.5 gpm	10 L/min.
Pilot Ratio	1.5:1	
Check Cracking Pressure	25 psi	1,7 bar
Factory Pressure Settings Established at	2 in ³ /min.	30 cc/min.
Maximum Valve Leakage at Reseat	5 drops/min.	0,3 cc/min.
Pilot Configuration	Sealed	
Series (from Cavity)	Series 1	
Valve Hex Size	7/8 in.	22,2 mm
Valve Installation Torque	30 - 35 lbf ft	40 - 50 Nm
Seal Kits - Cartridge	Buna: 990-011-007	
Seal Kits - Cartridge	Viton: 990-011-006	
Model Weight	0.27 lb.	0.12 kg.



CBAB-XNN

Fixed Pressure Range

Standard Options

- N 2900 - 3500 psi (200 - 245 bar)
- P 2250 - 2680 psi (155 - 185 bar)

Seal Material

Standard Options

- N Buna-N
- V Viton