





Pilot-to-open check valve with standard pilot

Capacity:
7.5 gpm (30 L/min.)

Model:
CKBG

Product Description

This valve is a pilot to open check valve. It has a sealed pilot, a steel seat, and is non-vented. It allows free flow from the valve (port 2) to the load (port 1) and blocks flow in the opposite direction. Pressure at the pilot (port 3) will open the valve from port 1 to port 2. Pilot pressure needed at port 3 to open the valve is directly proportional to the load pressure at port 1. Pressure at port 2 directly opposes pilot pressure.




Technical Features

- Provides hose break protection, prevents loads from drifting and positively locks pressurized loads.
- Extremely low leakage. The seat and poppet are heat treated for long life. If the load drifts due to the valve, the seat has probably been damaged by contamination and the valve should be replaced.
- Sealed pilot for use in circuits where cross port leakage is undesirable.
- Note: Available only with 30 psi or 75 psi (2 bar or 5 bar) check valve cracking pressures.
- Pilot-to-open check cartridges are locking valves, not motion control valves. For motion control applications, use counterbalance valves.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

Technical Data

	U.S. Units	Metric Units
Cavity	T-163A	
Capacity	7.5 gpm	30 L/min.
Pilot Ratio	3:1	
Maximum Operating Pressure	5000 psi	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.	0,07 cc/min.
Series (from Cavity)	Series 0	
Valve Internal Hex Size	5/16 in.	8 mm
Valve Installation Torque	20 - 25 lbf ft	27 - 33 Nm
Seal Kits - Cartridge	Buna: 990-163-007	
Seal Kits - Cartridge	Viton: 990-163-006	
Model Weight	0.13 lb.	0.06 kg.



CKBG-XCN

Control	Bias Pressure	Seal Material
Standard Options	Standard Options	Standard Options
X Not Adjustable, Standard Hydraulic Pilot	C 30 psi (2 bar) E 75 psi (5 bar)	N Buna-N V Viton