


MODEL COBA

Pilot-to-close check valve CAPACITY: 40 L/min. | CAVITY: T-163A



CONFIGURATION

X Control Standard Pilot
 C Cracking Pressure 30 psi (2 bar)
 N Seal Material Buna-N



This valve is a spring biased closed, pilot-to-close check cartridge that has a 3:1 pilot ratio. The valve allows flow from port 1 to port 2 and blocks reverse flow. Pressure at the pilot port opposes pressure at port 1 at a ratio of 3:1. This valve is most often used in regeneration circuits.

TECHNICAL DATA

Cavity T-163A		
Series	0	
Capacity	40 L/min.	
Pilot Ratio	3:1	
Maximum Operating Pressure	350 bar	
Maximum Valve Leakage at 110 SUS (24 cSt)	e Leakage at 110 SUS (24 cSt) 0,07 cc/min.	
Valve Hex Size	19,1 mm	
Valve Installation Torque	27 - 34 Nm	
Seal kit - Cartridge	Buna: 990-163-007	
Seal kit - Cartridge	Polyurethane: 990-163-002	
Seal kit - Cartridge	Viton: 990-163-006	
Model Weight	0.09 kg.	

SYMBOLS







TECHNICAL FEATURES

- Features hardened steel seats for excellent wear characteristics and contamination tolerance.
- Product is not available with A and B spring ranges (4 and 15 psi (0,3 and 1 bar)).
- Pressure at the port 2 area directly opposes pilot pressure.
- Reverse flow through the valve from port 2 to port 1 is not possible under any condition.
- Nominal pilot ratio is 3:1. This means that a pressure of 1000 psi (70 bar) at the pilot port will close a valve against a pressure of 3000 psi (205 bar) at port 1. Any decay or loss of pilot pressure could allow the valve to open, even if it is a momentary decay or loss.

• Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES





CONFIGURATION OPTIONS

CONTROL		
В	External 1/4 BSPP Pilot Port, Port 3 blocked	
X	Standard Pilot	
CRACKING PRESSURE		
C	30 psi (2 bar)	
D	50 psi (3,5 bar)	
E	75 psi (5 bar)	
F	100 psi (7 bar)	
SEAL MATERIAL		
N	Buna-N	
V	Viton	
	B X CRACKING C D E F SEAL MATE	

Copyright © 2002-2014 Sun Hydraulics Corporation. All rights reserved.