

### Free flow nose to side check valve


Capacity: 20 gpm (80 L/min.)

Model: CXDA

#### Product Description

Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.






#### Technical Features


- Two-port check valves share the same cavity for a given frame size, however, pay close attention as flow paths may be in opposite directions.
- Check valves offer extremely low leakage rates with a maximum leakage of less than 1 drop per minute (0,07 cc/min).
- Will accept 5000 psi (350 bar) at ports 1 and 2.

- Corrosion resistant cartridge valves are intended for use in corrosive environments and are identified by the model code suffix /AP (see Option Selection below). External parts are made from stainless steel with titanium or brass components, where applicable. Internal parts are made from carbon steel leaded alloy, the same as standard valves. For further details, please see the Materials of Construction page.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

## Technical Data

Technical Data		
	U.S. Units	Metric Units
Cavity	T-13A	
Capacity	20 gpm	80 L/min.
Maximum Operating Pressure	5000 psi	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.	0,07 cc/min.
Series (from Cavity)	Series 1	
Valve Hex Size	7/8 in.	22,2 mm
Valve Installation Torque	30 - 35 lbf ft	40 - 50 Nm
Seal Kits - Cartridge	Buna: 990-010-007	
Seal Kits - Cartridge	Viton: 990-010-006	
Model Weight	0.24 lb.	0.11 kg.





# CXDA-XCN

Control	Cracking Pressure	Seal Material	Material/Coating Modifier
Preferred Options	Preferred Options	Preferred Options	Preferred Options
X Not Adjustable	A 4 psi (0,3 bar) C 30 psi (2 bar) Standard Options	N Buna-N Standard Options	No modifier (standard material with no special coating)  Special Options
B 15 psi (1 bar) D 50 psi (3,5 bar) E 75 psi (5 bar) F 100 psi (7 bar)	V Viton	/AP Stainless Steel, Passivated  Control: X  Our stainless product line is growing! If you are interested in a stainless option for this model which is not shown please contact Sun.	
Additional Options			
Control	Crack	king Pressure	Seal Material

G 150 psi (10,5 bar) Handknob Manual Override 1 psi (0,07 bar)

When the modifier is /AP, the control must be  $\boldsymbol{X}$ 

| | | | | | Copyright © 2009-2010 Sun Hydraulics Corporation. All rights reserved.

Terms and Conditions - ISO Certification - Statement of Privacy