



MODEL
DMDB

Value Series, 3-way, solenoid-operated directional spool valve - 3600 psi (250 bar)
CAPACITY: 40 L/min. | CAVITY: T-11A



CONFIGURATION

X	Control	No Manual Override
A	Spool Configuration	Normally Open 1 to 2, Closed 2 to 3
N	Seal Material	Buna-N
(none)	Coil	No coil

NOTES

Please verify cartridge clearance requirements when choosing a Sun manifold. Different valve controls and coils require different clearances.

An additional 2.00 inches (50,8 mm) beyond the valve extension is needed for coil installation and removal.


This solenoid-operated 3-way, 2-position cartridge is a direct-acting, balanced spool directional valve.

TECHNICAL DATA


Cavity	T-11A
Series	1
Capacity	40 L/min.
Maximum Operating Pressure	250 bar
Response Time - Typical	50 ms
Maximum Valve Leakage at 110 SUS (24 cSt)	80 cc/min.@210 bar
Switching Frequency	15000 cycles/hr
Manual Override Force Requirement	66 N/100 bar @ Port 1
Manual Override Stroke	2,5 mm
Solenoid Tube Diameter	12,7 mm
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990-811-007
Seal kit - Cartridge	Viton: 990-811-006
Model Weight	0.20 kg.

SYMBOLS


X-Control, A-Spool




X-Control, N-Spool



M-Control, A-Spool




M-Control, N-Spool



TECHNICAL FEATURES

- This valve is direct actuated and requires no minimum hydraulic pressure for operation.
- The solenoid tube assembly is fatigue rated for 3600 psi (250 bar) service.
- Port 2 and 3 are the preferred inlets for this valve. Port 1 has limited capacity.
- This valve utilizes a wet armature design. This means that the working fluid surrounds the armature and is exposed to the heat generated by the coil. This can be a factor if the coil is energized for long periods of time. Some fluids, notably water/glycol mixtures, break down at these temperatures over time and form varnishes that will affect the function of the cartridge.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES



CONFIGURATION OPTIONS

CONTROL		
Standard Options	M	Manual Override
	X	No Manual Override
SPOOL CONFIGURATION		
Standard Options	A	Normally Open 1 to 2, Closed 2 to 3
	N	Normally Open 2 to 3, Closed 1 to 2
SEAL MATERIAL		
Standard Options	N	Buna-N
	V	Viton

COIL

Standard Options		No coil
	212N	DIN 43650 3 pin (Hirschman), 12 VDC, no transient voltage suppression (TVS) diodes
	224N	DIN 43650 3 pin (Hirschman), 24 VDC, no transient voltage suppression (TVS) diodes
	712N	Twin Lead, 12 VDC, no transient voltage suppression (TVS) diodes
	724N	Twin Lead, 24 VDC, no transient voltage suppression (TVS) diodes
	912N	Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes
	924N	Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes

Copyright © 2002-2014 Sun Hydraulics Corporation. All rights reserved.