

2-way, direct-acting, fixed setting, directional valve with drain to port 4 - normally closed

Functional Group:



Products : Cartridges : Directional; DP, DR**, DV** : 2 Way - 4 Port - Normally Closed : Direct Acting - Fixed Setting**

Capacity:
7 gpm (28 L/min.)

Model:
DRBNX

Product Description

Normally closed, direct-acting, 2-way directional cartridges are switching devices typically used in moderate flow circuits. They can be used by themselves or to actuate larger pilot-operated directional cartridges or logic cartridges. The valve shifts when the pressure differential between port 1 and port 4 exceeds the setting.




Technical Features

- Port 3 can be used as a work port.
- The flow path between port 2 and port 3 is bidirectional.
- Because of their direct-acting design, these cartridges feature low internal leakage and low pilot flow consumption.
- Direct-acting and pilot-operated versions of these valves are interchangeable. They fit the same cavities and have the same flow paths.
- Pressure at port 4 is directly additive to the setting of the valve.
- This valve is not bistable; it is capable of modulating between the two positions shown.
- Maximum pressure at port 3 should be limited to 3000 psi (210 bar). This is due to fatigue strength limits not hydraulic operating limits.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

Technical Data

	U.S. Units	Metric Units
Cavity	T-21A	
Capacity	7 gpm	28 L/min.
Factory Pressure Settings Established at	4 gpm	15 L/min.
Maximum Operating Pressure	5000 psi	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	2 in ³ /min.	30 cc/min.
Series (from Cavity)	Series 1	
Valve Hex Size	7/8 in.	22,2 mm
Valve Installation Torque	30 - 35 lbf ft	40 - 50 Nm
Seal Kits - Cartridge	Buna: 990-021-007	
Seal Kits - Cartridge	Viton: 990-021-006	
Model Weight	0.33 lb.	0.15 kg.



DRBN-XFN

Shifting Pressure		Seal Material	
Standard Options		Standard Options	
F	100 psi (7 bar)	N	Buna-N
		V	Viton