

1

2

3

4

5

6

Other flow ranges / drawings:

Serie 1 - 23lpm - L02654

Serie 2 - 45lpm - L02656

Serie 3 - 95lpm - L02658

Serie 4 - 200lpm - L02660*

Ports:

1, 2 = G1 1/4"

3 = G1"

4, G = G1/4"

Port 3 G1"

x2 Ø10,4 ∇ through

Port G G1/4"

76,2


0

Port 1 G1 1/4"

127

0

149,2



~260

Port 4 G1/4"

Port 2 G1 1/4"

12,7

0

34,9

136,5

Pos. 4 can be exchanged to another voltage and/or contact type (i.e. Deutsch)

Pos. 3 can be exchanged to normally open and/or soft shift version

4	1	770-224	Solenoid 770-224 24VDC	270-0006	0,3	0,5 Nm
3	1	DAAL-MCN	Directional valve T-8A	260-0045	0,21	35-40 Nm
2	1	FVFA-8IN T-24A	Prioritetsventil ventstyr	214-0120	1,33	500 Nm
1	1	QAY/S T-24A	Ventilhus G1/4"	224-1212	7,8	2 x M10
#	Qty	Part Number	Description	Hydnet art nr	[kg]	Installation

ISO 2768-1 Medium, Ra=3,2µm □ Stamp framed text on surface, height = 4mm. Sharp edges chamfered.		Material SG Iron	Heat treat, finish -	Status RELEASED	Dimensions ~150x127x77	Block -	Hydnet art nr -
Design OBD		Drawn OBD	Check PIL	Net. weight ~10 kg	See drawing 3D02659		
Title Regenerativ krets Serie 4 200lpm, elstyd		Scale 1:2	Size A3	Created date 2011-09-13	Drawing L02660.icd		Sheet 1(1) Rev. -

SCALE 1 : 4