

Pilot-to-close, spring biased closed, unbalanced poppet logic element with metering notches and position switch

Capacity:
40 gpm (160
L/min.)

Functional Group:



Products : Cartridges : Logic Element : Unbalanced Poppet : Pilot-to-close, Spring Biased Closed with Metering Notches and Position Indicating Switch

Model:
LOGCZ

Product Description

These unbalanced, pilot-to-close logic valves are 2-way switching elements that are spring biased closed. Pressure at either work port 1 or 2 will oppose the spring and tend to open the valve while pressure at port 3 will tend to close it. The force generated by the pressure at port 3, plus the spring force, must be greater than the sum of the forces generated by the pressures at ports 1 and 2 for the valve to remain closed.

This valve incorporates a position switch to provide confirmation that the valve is closed.



View A-A
Pin Diagram

Schematic

Technical Features


- This valve has metering notches in the poppet to reduce hydraulic shock during valve opening and closing.
- The position switch in this valve provides confirmation that the valve is closed.
- These valves have positive seals between port 2 and the pilot area.
- This cartridge is supplied as a sealed, factory set unit and is not field serviceable. Any tampering will violate the product warranty.
- When torquing this cartridge into its cavity, a crow's foot wrench or similar will be required since the position switch precludes the use of a deep socket wrench.
- Because these valves are unbalanced, operation is pressure dependent. Opening and closing of the poppet are functions of the force balances on three areas: Port 1 = 100%, Port 2 = 80%, and the Pilot Area = 180%.
- These valves are pressure responsive at all ports, therefore it is essential to consider all aspects of system operation through a complete cycle. Pressure changes at any one port may cause a valve to switch from a closed to an open position, or vice versa. All possible pressure changes in the complete circuit must be considered to assure a safe, functional system design.
- All ports will accept 5000 psi (350 bar).
- Position switch is CE approved.
- An optional protective cover, with mounting hardware included, may be ordered separately. See kit number: 991-043.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

Technical Data

	U.S. Units	Metric Units
Cavity	T-17A	
Capacity	40 gpm	160 L/min.
Area Ratio, A3 to A1	1.8:1	
Area Ratio, A3 to A2	2.25:1	
Maximum Operating Pressure	5000 psi	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.	0,07 cc/min.
Pilot Passage into Valve	.06 in.	1,50 mm
Pilot Volume Displacement	.25 in ³	4,1 cc
Series (from Cavity)	Series 3	
Transition leakage at 110 SUS (24 cSt)	2 in ³ /min.@1000 psi	30 cc/min.@70 bar
Valve Hex Size	1 1/4 in.	31,8 mm
Valve Installation Torque	150 - 160 lbf ft	200 - 215 Nm
Seal Kits - Cartridge	Buna: 990-017-007	
Seal Kits - Cartridge	Viton: 990-017-006	
Model Weight	1.99 lb.	0.90 kg.

Switch Specifications

	U.S. Units	Metric Units
Supply Voltage	20-30 VDC	
Reverse Polarity Protection	Yes	
Maximum Output Load	≤ 400 mA, Duty Ratio 100%	
Short Circuit Protection	Yes, Load Short Unlimited	
Turn On Time	≤ 25 ms	
Hysteresis	≤ .002 in.	
Operating Temperature Range	-25 to 80 °C	
Thermal Shift - 0 to 80 °C ≤ ±	.004 in.	0,1 mm
EMC	DIN EN 61000-6-1/2/3/4	
Connector Environment Rating	IP65	
Vibration	≥ 50g, 0-500 impulses/sec	
Shock	>50 g, 1ms	
Connector	M12 X 1 (4) Pin	



LOGC-ZDN

Nominal Control Pressure	Seal Material
Standard Options	Standard Options
D 50 psi (3,5 bar)	N Buna-N
	V Viton