



Cartridge Series Table

Series	SUN Cavities	Number of Ports
Series Z Cartridges 3/16" (4,8 mm) Internal Hex 3/8-24 UNF Thread Installation Torque: 100-120 lbf in. (11-14 Nm)	T-382A	2-Port
Series P Cartridges 7/8" (22,4 mm) Hex M16 Thread Installation Torque: 20-25 lbf ft. (27-33 Nm)	T-8A T-9A	2-Port 3-Port
Series 0 Cartridges 3/4" (19,1 mm) Hex M16 Thread Installation Torque: 20-25 lbf ft. (27-33 Nm)	T-162A T-163A	2-Port 3-Port
Series 1 Cartridges 7/8" (22,2 mm) Hex M20 Thread Installation Torque: 30-35 lbf ft. (40-50 Nm)	T-10A T-13A T-11A T-21A T-31A T-51A T-61A	2-Port 2-Port 3-Port 4-Port 4-Port 6-Port 6-Port
Series 2 Cartridges 1-1/8" (28,6 mm) Hex 1"-14 UNS Thread Installation Torque: 45-50 lbf ft. (60-70 Nm)	T-3A T-5A T-2A T-22A T-32A T-52A T-62A	2-Port 2-Port 3-Port 4-Port 4-Port 6-Port 6-Port
Series 3 Cartridges 1-1/4" (31,8 mm) Hex M36 Thread Installation Torque: 150-160 lbf ft. (200-215 Nm)	T-16A T-17A T-23A T-33A T-53A T-63A	2-Port 3-Port 4-Port 4-Port 6-Port 6-Port
Series 4 Cartridges 1-5/8" (41,3 mm) Hex M48 Thread Installation Torque: 350-375 lbf ft. (475-500 Nm)	T-18A T-18AU T-19A T-19AU T-24A T-34A T-64A	2-Port 2-Port 3-Port 3-Port 4-Port 4-Port 6-Port