





Pilot operated, pressure reducing/relieving valve

Capacity:
40 gpm (160 L/min.)

Model:
PPHB

Product Description

Pilot-operated, pressure reducing/relieving valves reduce a high primary pressure at the inlet (port 2) to a constant reduced pressure at port 1, with a full-flow relief function from port 1 to tank (port 3).



Technical Features





- Maximum pressure at port 3 should be limited to 3000 psi (210 bar).
- Pressure at port 3 is directly additive to the valve setting at a 1:1 ratio and should not exceed 3000 psi (210 bar).
- Pilot operated reducing, reducing/relieving valves by nature are not fast acting valves. For superior dynamic response, consider direct acting valves.
- Recommended maximum inlet pressure is determined by the adjustment range. Ranges D, E, N, and Q are tested with a 2000 psi (140 bar) maximum differential between inlet and reduced pressure. Ranges A, B, and H are tested with a 3000 psi (210 bar) maximum differential between inlet and reduced pressure. Ranges C and W are tested with 5000 psi (350 bar) of inlet pressure.
- Pilot operated valves exhibit exceptionally flat pressure/flow characteristics, are very stable and have low hysteresis.
- All three-port pressure reducing and reducing/relieving cartridges are physically interchangeable (i.e. same flow path, same cavity for a given frame size). When considering mounting configurations, it is sometimes recommended that a full capacity return line (port 3) be used with reducing/relieving cartridges.
- Full reverse flow from reduced pressure (port 1) to inlet (port 2) may cause the main spool to close. If reverse free flow is required in the circuit, consider adding a separate check valve to the circuit.
- If pilot flow consumption is critical, consider using direct acting reducing/relieving valves.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

Special Notes

- Maximum pressure differentials for spring ranges: A and B are 3000 psi (210 bar) N and Q are 2000 psi (140 bar) W is 5000 psi (350 bar) inlet pressure

Technical Data

	U.S. Units	Metric Units
Cavity	T-17A	
Capacity	40 gpm	160 L/min.
Control Pilot Flow	15 - 20 in ³ /min.	0,25 - 0,33 L/min.
Factory Pressure Settings Established at	blocked control port (dead headed)	
Maximum Operating Pressure	5000 psi	350 bar
Series (from Cavity)	Series 3	
Adjustment - Number of Clockwise Turns to Increase Setting	5	
Valve Hex Size	1 1/4 in.	31,8 mm
Valve Installation Torque	150 - 160 lbf ft	200 - 215 Nm
Adjustment Screw Internal Hex Size	5/32 in.	4 mm
Adjustment Locknut/Cap Hex Size	9/16 in.	15 mm
Adjustment Nut Torque	80 - 90 lbf in.	9 - 10 Nm
Seal Kits - Cartridge	Buna: 990-017-007	
Seal Kits - Cartridge	Viton: 990-017-006	
Model Weight	1.24 lb.	0.56 kg.



PPHB-LAN

Control	Adjustment Range	Seal Material	Material/Coating Modifier
Preferred Options	Preferred Options	Preferred Options	Preferred Options
L Standard Screw Adjustment	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting	N Buna-N	No modifier (standard material with no special coating)
Standard Options		Standard Options	Special Options
C* Tamper Resistant - Factory Set	W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting	V Viton	/ AP Stainless Steel, Passivated
K Handknob	Standard Options		Control:C
	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting		Control:L
	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting		
	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting		

Our stainless product line is growing! If you are interested in a stainless option for this model which is not shown please contact Sun.

Additional Options

Control

Adjustment Range

Seal Material

Q*	Capped and Lockwired	C	150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting
		D	25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting
		E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting
		H	30 - 3000 psi (2 - 210 bar), 200 psi (14 bar) Standard Setting

When the modifier is /AP, the control must be C or L

* Special Setting required, specify at time of order
Customer specified setting stamped on hex.

Related Models
[PPHB8](#)