



Direct-acting, pressure reducing/relieving main stage piloted from port 4



Capacity:
10 gpm (40 L/min.)

Model:
PSDT

Product Description

The direct-acting reducer/reliever main section is meant to act as an interface between a low flow pressure source at port 4 and a circuit with higher flow requirements. The valve will reduce a high primary pressure at the inlet (port 2) to a reduced pressure at port 1, with a full-flow relief function from port 1 to tank (port 3).

The valve incorporates a damped construction for stable operation allowing the use of high reduced pressure.





Technical Features

- The valve is biased to the relieving mode with a 100 psi (7 bar) spring. Pressure at port 4 is directly added to the setting of the valve once this threshold is exceeded. For example, 1000 psi (70 bar) at port 4 will result in a setting of 900 psi (63 bar) at port 1.
- Maximum pressure at port 3 should be limited to 3000 psi (210 bar).
- All spring ranges are tested for correct operation with 5000 psi (350 bar) inlet pressure.
- Suitable for accumulator circuits since the absence of pilot control flow results in reduced secondary circuit leakage.
- Direct acting concept provides highly reliable operation in contaminated systems, especially at dead headed conditions.
- Direct operated version offers superior dynamic response compared to equivalent pilot operated models.
- Pressure on the drain (port 4) is directly additive to the valve setting at a 1:1 ratio and should not exceed 5000 psi (350 bar).
- Leakage specified in Technical Data is out of port 3 with a supply pressure of 2000 psi (140 bar) and the valve set at mid range. This leakage is directly proportional to pressure differential and inversely proportional to viscosity expressed in centistokes.
- Full reverse flow from reduced pressure (port 1) to inlet (port 2) may cause the main spool to close. If reverse free flow is required in the circuit, consider adding a separate check valve to the circuit.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

Technical Data

	U.S. Units	Metric Units
Cavity	T-21A	
Capacity	10 gpm	40 L/min.
Maximum Operating Pressure	5000 psi	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	2.5 in ³ /min.	41 cc/min.
Series (from Cavity)	Series 1	
Valve Hex Size	7/8 in.	22,2 mm
Valve Installation Torque	30 - 35 lbf ft	40 - 50 Nm
Seal Kits - Cartridge	Buna: 990-021-007	
Seal Kits - Cartridge	Viton: 990-021-006	
Model Weight	0.37 lb.	0.17 kg.



PSDT-XFN

Control

Standard Options

X Not Adjustable

Bias Pressure

Standard Options

F 100 psi (7 bar)

Seal Material

Standard Options

N Buna-N
V Viton