





Pilot operated, pressure reducing/relieving main stage with integral T-8A control cavity and drain to port 4

Capacity:
40 gpm (160
L/min.)

Model:
PVHA8

Product Description

This valve is a 3-way, normally open modulating element, externally drained, that incorporates an integral pilot control cavity. The pilot control cavity will accept any T-8A pressure control cartridge. The valve reduces a high primary pressure at the inlet (port 2) to a constant reduced pressure at port 1, with a full flow relief function from port 1 to tank (port 3). The pilot cartridge's setting determines the difference in pressure between reduced pressure (port 1) and the drain (port 4).





Technical Features

- Maximum pressure at port 3 should be limited to 3000 psi (210 bar).
- Pilot operated valves exhibit very low dead-band transition between reducing and relieving modes.
- Pressure at port 4 should not exceed 5000 psi (350 bar).
- Pilot operated valves exhibit exceptionally flat pressure/flow characteristics, are very stable and have low hysteresis.
- Maximum inlet pressure is determined by the bias spring. The D spring is tested with 2000 psi (140 bar) maximum differential pressure and the W spring is tested with 5000 psi (350 bar) maximum inlet pressure.
- NOTE: With the -8 control option, the main stage valve should first be installed to the correct torque value. The T-8A pilot control valve should then be installed into the main stage valve to its required torque value.
- The -8 control option allows the pilot control valve to be incorporated directly into the end of the relief cartridge via the T-8A cavity. These pilot control cartridges are sold separately and include electro-proportional, solenoid, air pilot, and hydraulic pilot operation. See Pilot Control Cartridges.
- Full reverse flow from reduced pressure (port 1) to inlet (port 2) may cause the main spool to close. If reverse free flow is required in the circuit, consider adding a separate check valve to the circuit.

- Pressure on the drain (port 4) is directly additive to the valve setting at a 1:1 ratio and should not exceed 5000 psi (350 bar).
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

Technical Data

	U.S. Units	Metric Units
Cavity	T-23A	
Capacity	40 gpm	160 L/min.
Control Pilot Flow	15 - 20 in ³ /min.	0,25 - 0,33 L/min.
Maximum Operating Pressure	5000 psi	350 bar
Pilot Control Cavity	T-8A	
Pilot Control Valve Hex Size	7/8 in.	22,2 mm
Pilot Control Valve Installation Torque	20 - 25 lbf ft	27 - 33 Nm
Series (from Cavity)	Series 3	
Valve Hex Size	1 1/4 in.	31,8 mm
Valve Installation Torque	150 - 160 lbf ft	200 - 215 Nm
Seal Kits - Cartridge	Buna: 990-023-007	
Seal Kits - Cartridge	Viton: 990-023-006	
Model Weight	1.32 lb.	0.60 kg.



PVHA-8WN

Minimum Control Pressure

Standard Options

- D 25 psi (1,7 bar)
- W 100 psi (7 bar)

Seal Material

Standard Options

- N Buna-N
- V Viton