





Direct-acting sequence valve with reverse flow check

Capacity:
15 gpm (60 L/min.)

Model:
SCCA

Product Description

Direct-acting sequence valves with reverse-flow check will supply a secondary circuit with flow once the pressure at the inlet (port 1) has exceeded the valve setting. Additionally, these valves incorporate an integral check valve to provide reverse flow from port 2 (sequence) to port 1 (inlet). The pressure setting of a sequence valve controls the pressure at port 1 relative to the pressure at the drain (port 3).







Technical Features

- Pressure at port 3 is directly additive to the valve setting at a 1:1 ratio and should not exceed 5000 psi (350 bar).
- Although this is a zero pilot flow valve, port 3 (drain) must be connected to maintain a pressure reference in the control chamber. If port 3 is blocked, reciprocating seal weepage will cause the valve to malfunction.
- All 3 port sequence cartridges are physically and functionally interchangeable (i.e. same flow path, same cavity for a given frame size).
- Suitable for use in load holding applications.
- Corrosion resistant cartridge valves are intended for use in corrosive environments and are identified by the model code suffix /AP (see Option Selection below). External parts are made from stainless steel with titanium or brass components, where applicable. Internal parts are made from carbon steel leaded alloy, the same as standard valves. For further details, please see the Materials of Construction page.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

Technical Data

	U.S. Units	Metric Units
Cavity	T-11A	
Capacity	15 gpm	60 L/min.
Check Cracking Pressure	25 psi	1,7 bar
Factory Pressure Settings Established at	2 in ³ /min.	30 cc/min.
Maximum Operating Pressure	5000 psi	350 bar
Maximum Valve Leakage at Reseat	10 drops/min.	0,7 cc/min.
Response Time - Typical	2 ms	
Series (from Cavity)	Series 1	
U.S. Patent #	4,834,135	
Adjustment - Number of Clockwise Turns to Increase Setting	5	
Valve Hex Size	7/8 in.	22,2 mm
Valve Installation Torque	30 - 35 lbf ft	40 - 50 Nm

Adjustment Screw Internal Hex Size	5/32 in.	4 mm
Adjustment Locknut/Cap Hex Size	9/16 in.	15 mm
Adjustment Nut Torque	80 - 90 lbf in.	9 - 10 Nm
Seal Kits - Cartridge	Buna: 990-011-007	
Seal Kits - Cartridge	Viton: 990-011-006	
Model Weight	0.44 lb.	0.20 kg.



SCCA-LAN

Control	Adjustment Range	Seal Material	Material/Coating Modifier
Preferred Options	Preferred Options	Preferred Options	Preferred Options
L Standard Screw Adjustment Standard Options	A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N Standard Options	No modifier (standard material with no special coating) Special Options
C* Tamper Resistant - Factory Set	W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting Standard Options	V Viton	/AP Stainless Steel, Passivated Control: C
	B 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) Standard Setting		Our stainless product line is growing! If you are interested in a stainless option for this model which is not shown please contact Sun. Control: E
	C 2000 - 6000 psi (140 - 420 bar), 2000 psi (140 bar) Standard Setting		
	D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting		
	E 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting		
Additional Options (Click Here)			
Control	Adjustment Range	Seal Material	
K Handknob			
When the modifier is /AP, the control must be C or L			
* Special Setting required, specify at time of order Customer specified setting stamped on hex.			