



- NOTES:
 1) MIN./MAX LS DEPTH = 26,9/88,9, FOR SAE-4, SAE-6, 1/4 AND 3/8 NPTF PLUGGED CONSTRUCTION PORTS.
 2) MIN./MAX LS DEPTH = 34,3/88,9, FOR 1/4 AND 3/8 BSPP PLUGGED CONSTRUCTION PORTS.

							TITLE T382A CAVITY			REV. E PART NO. T-382, METRIC		
					DIM. TOLERANCE ± 0,13 mm UNLESS SPECIFIED		SCALE 4:1		REF. CSZN-XY* CXZA-X**		MATERIAL	
					ANGLE TOL ± 1/2 FINISH 2,0 UNLESS SPECIFIED		DRAWN ALI		CHECK		RELEASE	
					REMOVE ALL BURRS		DATE 13APR06		DATE		DATE	
E REVISED CAVITY TOOLING P/N. REVISED DIMS FOR CAVITY / TOOLING CONSISTENCY. ADDED METRIC TOL. BLOCK TO SHEET 2					06JUN11		JRS RCL 10164		CORPORATION 1500 WEST UNIVERSITY PKWY SARASOTA, FLORIDA 34243, USA TELEPHONE (941) 362-1200			
REVISION					DATE		DRN					