





Port 1 to 2 open, port 3 blocked cavity plug

Capacity:

Model:
XEOA

Product Description

This cavity plug allows ports 1 and 2 to remain open and blocks port 3.



Technical Features

- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see Option Selection below). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.

Technical Data

	U.S. Units	Metric Units
Cavity	T-11A	
Series (from Cavity)	Series 1	
Valve Hex Size	7/8 in.	22,2 mm
Valve Installation Torque	30 - 35 lbf ft	40 - 50 Nm
Seal Kits - Cartridge	Buna: 990-011-007	
Seal Kits - Cartridge	Viton: 990-011-006	
Model Weight	0.20 lb.	0.09 kg.

XEOA-XXN

Control		Adjustment Range		Seal Material		Material/Coating Modifier
Standard Options		Standard Options		Standard Options		Preferred Options
X	-	X	-	N	Buna-N	No modifier (standard material with no special coating) Special Options
				V	Viton	

/AP Stainless Steel, Passivated

Control:X

Our stainless product line is growing! If you are interested in a stainless option for this model which is not shown please contact Sun.

When the modifier is /AP, the control must be X