



TECHNICAL DATA

Body Type	Sandwich
Interface	ISO 05 - X&Y
Body Features	Tap in manifold - A and B
Stack Height	25 mm

NOTES

- Stack height value in technical data table includes seal retainer plate.
- This installation requires a retainer and seal kit which are purchased separately. See "Used With" section.
- **Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

CONFIGURATION OPTIONS

Model Code Example: ZSQ

Modifiers	Ports
ZSQ	Gage Ports: 1/4" BSPP;

MODIFIER

6061-T651 Aluminum, Buna-N

IS 65-45-12 Ductile Iron, Buna-N, Blackened

USED WITH

What models can this kit be used with?

- [990-120-009](#) ISO 05 X and Y US sandwich manifold retainer and buna-N seal kit
- [990-120-010](#) ISO 05 X and Y US sandwich manifold retainer and Viton seal kit
- [990-120-011](#) ISO 05 X and Y Europe sandwich manifold retainer and Viton seal kit
- [990-120-012](#) ISO 05 X and Y Europe sandwich manifold retainer and buna-N seal kit

MANIFOLD FACES

FACE GRID

1	2	3	4
5	6	7	8
9	10	11	12

Face 2



Face 5



Face 6

□

Face 7

□

Face 10

□